

# Package ‘diffviewer’

September 10, 2020

**Title** HTML Widget to Show File Differences

**Version** 0.1.0

**Description** A HTML widget that shows differences between files  
(text, images, and data frames).

**License** MIT + file LICENSE

**URL** <https://github.com/r-lib/diffviewer>

**BugReports** <https://github.com/r-lib/diffviewer/issues>

**Imports** htmlwidgets, jsonlite

**Suggests** covr, shiny

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Author** Hadley Wickham [aut, cre],  
Joshua Kunst [aut],  
Winston Chang [aut],  
RStudio [cph],  
Paul Fitzpatrick [cph] (Author of included daff.js library),  
Rodrigo Fernandes [cph] (Author of included diff2html library),  
JQuery Foundation [cph] (Author of included jquery library),  
Kevin Decker [cph] (Author of included jsdiff library),  
Matthew Holt [cph] (Author of included PapaParse library),  
Huddle [cph] (Author of included resemble library)

**Maintainer** Hadley Wickham <hadley@rstudio.com>

**Repository** CRAN

**Date/Publication** 2020-09-10 14:50:08 UTC

## R topics documented:

visual_diff . . . . .	2
visual_diff_output . . . . .	3

---

visual_diff	<i>HTML widget to visually compare two files</i>
-------------	--

---

## Description

Currently supports:

- image diffs for .svg and .png
- tabular diffs for .csv
- text diffs for everything else

## Usage

```
visual_diff(file_old, file_new, width = NULL, height = NULL)
```

## Arguments

file\_old, file\_new  
Paths to files to compare

width, height  
Output size

## Value

A HTML widget

## See Also

[visual\\_diff\\_output\(\)](#) for use within Shiny apps

## Examples

```
path1 <- tempfile()
path2 <- tempfile()
writeLines(letters, path1)
writeLines(letters[-13], path2)

if (interactive()) {
  visual_diff(path1, path2)
}
```

---

visual\_diff\_output     *Shiny bindings for visual\_diff()*

---

### Description

Use `visual_diff_output()` in ui and `render_visual_diff(visual_diff(...))` in the server function.

### Usage

```
visual_diff_output(outputId, width = "100%", height = "400px")
```

```
visual_diff_render(expr, env = parent.frame(), quoted = FALSE)
```

### Arguments

<code>outputId</code>	output variable to read from
<code>width, height</code>	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
<code>expr</code>	An expression that generates a <code>visual_diff</code>
<code>env</code>	The environment in which to evaluate <code>expr</code> .
<code>quoted</code>	Is <code>expr</code> a quoted expression (with <code>quote()</code> )? This is useful if you want to save an expression in a variable.

### Value

Components for use inside a Shiny app.

### Examples

```
if (require("shiny") && interactive()) {
  ui <- fluidPage(
    visual_diff_output("diff")
  )

  server <- function(input, output, session) {
    path1 <- tempfile()
    path2 <- tempfile()
    writeLines(letters, path1)
    writeLines(letters[-13], path2)

    output$diff <- visual_diff_render(visual_diff(path1, path2))
  }

  shinyApp(ui, server)
}
```

# Index

`visual_diff`, 2  
`visual_diff_output`, 3  
`visual_diff_output()`, 2  
`visual_diff_render`  
    (`visual_diff_output`), 3