

Package ‘httpcode’

November 14, 2016

Title 'HTTP' Status Code Helper

Description Find and explain the meaning of 'HTTP' status codes.
Functions included for searching for codes by full or partial number,
by message, and get appropriate dog and cat images for many
status codes.

Version 0.2.0

License MIT + file LICENSE

URL <https://github.com/sckott/httpcode>

BugReports <http://www.github.com/sckott/httpcode/issues>

RoxygenNote 5.0.1

NeedsCompilation no

Author Scott Chamberlain [aut, cre]

Maintainer Scott Chamberlain <myrmecocystus@gmail.com>

Repository CRAN

Date/Publication 2016-11-14 21:32:47

R topics documented:

httpcode-package	2
cat_for_status	2
http	3
Index	5

httpcode-package *Explain the meaning of HTTP status codes*

Description

Explain the meaning of HTTP status codes

Author(s)

Scott Chamberlain <myrmecocystus@gmail.com>

cat_for_status *Use cat or dog pictures for various HTTP status codes*

Description

Use cat or dog pictures for various HTTP status codes

Usage

```
cat_for_status(code, browse = FALSE)
```

```
dog_for_status(code, browse = FALSE)
```

Arguments

code An http status code

browse (logical) If TRUE, opens image in default browser. If FALSE, returns the URL of the image.

Details

uses a service for cats (<https://http.cat>) and dogs (<https://httpstatusdogs.com>)

Value

Opens image in your default browser, or returns URL

Examples

```
## Not run:
# give back url
cat_for_status(100)
dog_for_status(100)
cat_for_status(301)
dog_for_status(301)
cat_for_status(400)
dog_for_status(400)

# open image in default browser
cat_for_status(400, browse=TRUE)

# not found
# cat_for_status(555)

## End(Not run)
```

http

Find out about http status codes

Description

Find out about http status codes

Usage

```
http_code(code = NULL, verbose = FALSE)
```

```
http_search(text = NULL, verbose = FALSE)
```

Arguments

code	(character) An http status code, or a regex search for HTTP status codes.
verbose	(logical) include verbose status code explanation. Default: FALSE
text	(character) A text string to search the messages or descriptions of HTTP status codes.

Value

on S3 object of class `http_code`, that is inside a list of the form:

- `status_code` - the status code
- `message` - very brief message explaining the code
- `explanation` - more verbose explanation, but still short
- `explanation_verbose` - the complete explanation

Examples

```
# search by code
http_code(100)
http_code(400)
http_code(503)
## verbose explanation
http_code(100, verbose = TRUE)
http_code(400, verbose = TRUE)
http_code(503, verbose = TRUE)

# fuzzy code search
http_code('1xx')
http_code('3xx')
http_code('30[12]')
http_code('30[34]')
http_code('30[34]')
## verbose explanation
http_code('1xx', verbose = TRUE)
http_code('3xx', verbose = TRUE)

# search by text message
http_search("request")
http_search("forbidden")
http_search("too")
## verbose explanation
http_search("request", verbose = TRUE)
```

Index

*Topic **package**

httpcode-package, [2](#)

cat_for_status, [2](#)

dog_for_status (cat_for_status), [2](#)

http, [3](#)

http_code (http), [3](#)

http_search (http), [3](#)

httpcode (httpcode-package), [2](#)

httpcode-package, [2](#)