

Package ‘netplot’

June 16, 2021

Title Beautiful Graph Drawing

Version 0.1-1

Description A graph visualization engine that puts an emphasis on aesthetics at the same time of providing default parameters that yield out-of-the-box-nice visualizations. The package is built on top of 'The Grid Graphics Package' and seamlessly work with 'igraph' and 'network' objects.

Depends R (>= 3.4.0)

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.1

Imports graphics, grDevices, igraph, network, sna, stats

Suggests knitr, rmarkdown, markdown, igraphdata, intergraph, ggraph, gridGraphics, ggplot2, gridExtra, gridBase, magrittr

VignetteBuilder knitr

URL <https://github.com/USCCANA/netplot>

BugReports <https://github.com/USCCANA/netplot/issues>

NeedsCompilation no

Author George Vega Yon [aut, cre] (<<https://orcid.org/0000-0002-3171-0844>>)

Maintainer George Vega Yon <g.vegayon@gmail.com>

Repository CRAN

Date/Publication 2021-06-16 07:10:02 UTC

R topics documented:

colorkey	2
colorRamp2	3
make_colors	5
netplot-formulae	6
nplot	7

nplot_base	11
npolygon	13
piechart	14
segments_gradient	16
set_gpar	17

Index	19
--------------	-----------

colorkey	<i>Function to create a color key</i>
----------	---------------------------------------

Description

Function to create a color key

Usage

```
colorkey(
  x0,
  y0,
  x1,
  y1,
  cols = c("white", "steelblue"),
  tick.range = c(0, 1),
  tick.marks = seq(tick.range[1], tick.range[2], length.out = 5L),
  label.from = NULL,
  label.to = NULL,
  nlevels = 100,
  main = NULL,
  relative = TRUE,
  tick.args = list(),
  label.args = list(),
  main.args = list()
)
```

Arguments

`x0`, `x1`, `y0`, `y1` Numeric scalars. Coordinates of the lower left and upper right points where the color key will be drawn as proportion of the plotting region.

`cols` Character scalar. Colors specifications to create the color palette.

`tick.range`, `tick.marks` Numeric vectors specifying the range and the tickmarks respectively.

`label.from`, `label.to` Character scalar. Labels of the lower and upper values of the color key.

`nlevels` Integer scalar. Number of levels to extrapolate.

`main` Character scalar. Title of the colorkey.

`relative` Logical scalar. When TRUE the color key is drawn relative to the plotting region area taking `x0`, `x1`, `y0`, `y1` as relative location.

`tick.args`, `label.args`, `main.args` Lists of arguments passed to `graphics::text` for drawing ticks, labels and main respectively.

Value

NULL.

Examples

```
set.seed(22231)

# A random figure
dat <- matrix(runif(100*3), ncol = 3)
col <- colorRamp2(c("blue", "white", "red"))

plot(
  dat[,1], dat[,2],
  col = rgb(col(dat[,3]), maxColorValue=255),
  cex=2, pch=20
)

# Pretty color key
colorkey(
  x0 = .60, y0 = .80,
  x1 = .95, y1 = .95,
  cols = c("blue", "white", "red"),
  main = "Some color scale"
)
```

colorRamp2 *A faster implementation of `grDevices::colorRamp` for linear interpolation.*

Description

A faster implementation of `grDevices::colorRamp` for linear interpolation.

Usage

```
colorRamp2(x, alpha = TRUE, thresholds = NULL)
```

Arguments

`x` A vector of colors.

alpha	Logical scalar. When TRUE This implementation of colorRamp can be 2 or more times faster than the grDevices version. It is intended for consecutive calls (i.e. in a loop) to improve performance. It is equivalent to the linear interpolation of the function colorRamp.
thresholds	A numeric vector of length length(x). Optional threshold levels so that the mixing can be different that even.

Value

A function as in [grDevices::colorRamp](#).

Examples

```
# Creating a function for 2 colors
myf <- colorRamp2(c("black", "steelblue"))
f <- colorRamp(c("black", "steelblue"))

plot.new()
plot.window(xlim = c(0,2), ylim = c(1, 11))

# These should be the same colors
rect(
  xleft = 0,
  xright = 1,
  ybottom = 1:10,
  ytop = 2:11,
  col = rgb(myf((1:10)/10), maxColorValue = 255)
)
rect(
  xleft = 1,
  xright = 2,
  ybottom = 1:10,
  ytop = 2:11,
  col = rgb(f((1:10)/10), maxColorValue = 255)
)

# Another example setting different thresholds
myf <- colorRamp2(c("black", "steelblue"))
myf2 <- colorRamp2(c("black", "steelblue"), thresholds=c(0, .7))

plot.new()
plot.window(xlim = c(0,2), ylim = c(1, 11))

# These should be the same colors
rect(
  xleft = 0,
  xright = 1,
  ybottom = 1:10,
  ytop = 2:11,
  col = rgb(myf((1:10)/10), maxColorValue = 255)
)
```

```

rect(
  xleft = 1,
  xright = 2,
  ybottom = 1:10,
  ytop = 2:11,
  col = rgb(myf2((1:10)/10), maxColorValue = 255)
)

```

make_colors

Create a vector of colors for vertices and edges

Description

Using vertex/edge attributes, these functions return vectors of colors that can be used either during the creation of the `nplot` object, or afterwards when changing `gpar` (graphical parameter) values with `set_gpar`.

Usage

```
make_colors(dat, categorical = FALSE, color_map = grDevices::hcl.colors)
```

```
make_edges_colors(x, eattr, ...)
```

```
make_vertex_colors(x, vattr, ...)
```

Arguments

<code>dat</code>	A vector of data to generate the color from.
<code>categorical</code>	Logical. When TRUE sets the colors as categories.
<code>color_map</code>	A function to generate a palette.
<code>x</code>	A graph of class <code>network</code> or <code>igraph</code> .
<code>...</code>	Further arguments passed to <code>make_colors</code> .
<code>vattr, eattr</code>	Character. Names of either vertex or edge variables to be used for generating the colors.

Details

If no attribute is provided, then by default the colors are set according to indegree.

`x` can be either a graph of class `igraph` or `network`.

Value

A vector of colors with the attribute `color_map`. The color map used to generate the colors.

Examples

```
data(UKfaculty, package="igraphdata")
col <- make_vertex_colors(UKfaculty, "Group")

if (require(magrittr)) {

  nplot(UKfaculty) %>%
    set_vertex_gpar("core", fill = col, col=col) %>%
    set_vertex_gpar("frame", fill = col, col=col, alpha=.7) %>%
    set_edge_gpar(col="gray50", fill="gray50", alpha=.5)
}
```

netplot-formulae *Formulas in netplot*

Description

Edge colors in both `nplot()` and `set_edge_gpar()` can be specified using a formula based on `ego()` and `alter()` (source and target). This way the user can set various types of combination varying the mixing of the colors, the alpha levels, and the actual mixing colors to create edge colors.

Usage

```
color_formula(x, col, alpha, env, type, mix = 1, postfix = NULL)
```

```
ego(...)
```

```
alter(...)
```

Arguments

<code>x</code>	An object of class <code>netplot</code> .
<code>col</code>	Any valid color. Can be a single color or a vector.
<code>alpha</code>	Number. Alpha levels
<code>env, type, postfix</code>	For internal use only.
<code>mix</code>	Number. For mixing colors between <code>ego</code> and <code>alter</code>
<code>...</code>	Passed to <code>color_formula</code> .

Value

Nothing. These functions are called internally when using formulas. `color_formula` modifies the environment `env`.

Examples

```

if (require(gridExtra) & require(magrittr)) {
  library(igraph)
  net <- make_ring(4)

  set.seed(1)
  np <- nplot(net, vertex.color = grDevices::hcl.colors(4), vertex.size.range=c(.1, .1))
  np %>% set_edge_gpar(lwd = 4)

  grid.arrange(
    np,
    np %>% set_edge_gpar(col =~ego + alter),
    np %>% set_edge_gpar(col =~ego(alpha=0) + alter),
    np %>% set_edge_gpar(col =~ego + alter(alpha=0)),
    np %>% set_edge_gpar(col =~ego(mix=0) + alter(mix=1)),
    np %>% set_edge_gpar(col =~ego(mix=1) + alter(mix=0))
  )
}

```

nplot

*Plot a network***Description**

Plot a network

Usage

nplot(...)

S3 method for class 'igraph'

```

nplot(
  x,
  layout = igraph::layout_nicely(x),
  vertex.size = igraph::degree(x, mode = "in"),
  vertex.label = igraph::vertex_attr(x, "name"),
  edge.width = igraph::edge_attr(x, "weight"),
  ...
)

```

S3 method for class 'network'

```

nplot(
  x,
  layout = sna::gplot.layout.kamadakawai(x, NULL),
  vertex.size = sna::degree(x, cmode = "indegree"),
  vertex.label = network::get.vertex.attribute(x, "vertex.names"),
  ...
)

```

```

## Default S3 method:
nplot(
  edgelist,
  layout,
  vertex.size = 1,
  bg.col = "transparent",
  vertex.nsidess = 15,
  vertex.color = grDevices::hcl.colors(1),
  vertex.size.range = c(0.01, 0.03),
  vertex.frame.color = grDevices::adjustcolor(vertex.color, red.f = 0.75, green.f =
    0.75, blue.f = 0.75),
  vertex.rot = 0,
  vertex.frame.prop = 0.2,
  vertex.label = NULL,
  vertex.label.fontsize = NULL,
  vertex.label.color = "black",
  vertex.label.fontfamily = "HersheySans",
  vertex.label.fontface = "bold",
  vertex.label.show = 0.3,
  vertex.label.range = c(5, 15),
  edge.width = 1,
  edge.width.range = c(1, 2),
  edge.arrow.size = NULL,
  edge.color = ~ego(alpha = 0.25) + alter,
  edge.curvature = pi/3,
  edge.line.lty = "solid",
  edge.line.breaks = 10,
  sample.edges = 1,
  skip.vertex = FALSE,
  skip.edges = FALSE,
  skip.arrows = skip.edges,
  add = FALSE,
  zero.margins = TRUE,
  ...
)

## S3 method for class 'netplot'
print(x, y = NULL, newpage = TRUE, ...)

```

Arguments

<code>x</code>	An igraph object.
<code>layout</code>	Numeric two-column matrix with the graph layout.
<code>vertex.size</code>	Numeric vector of length <code>vcount(x)</code> . Absolute size of the vertex.
<code>vertex.label</code>	Character vector of length <code>vcount(x)</code> . Labels.
<code>edge.width</code>	Vector of length <code>ecount(x)</code> .

<code>edgelist</code>	An edgelist.
<code>bg.col</code>	Color of the background.
<code>vertex.nsid</code>	Numeric vector of length <code>vcount(x)</code> . Number of sides of the vertex. E.g. three is a triangle, and 100 approximates a circle.
<code>vertex.color</code>	Vector of length <code>vcount(x)</code> . Vertex colors.
<code>vertex.size.range</code>	Vector of length <code>vcount(x)</code> .
<code>vertex.frame.color</code>	Vector of length <code>vcount(x)</code> .
<code>vertex.rot</code>	Vector of length <code>vcount(x)</code> . Passed to <code>npolygon</code> , elevation degree from which the polygon is drawn.
<code>vertex.frame.prop</code>	Vector of length <code>vcount(x)</code> . What proportion of the vertex does the frame occupy (values between 0 and 1).
<code>vertex.label.fontSize</code>	Numeric vector.
<code>vertex.label.color</code>	Vector of colors of length <code>vcount(x)</code> .
<code>vertex.label.fontfamily</code>	Character vector of length <code>vcount(x)</code> .
<code>vertex.label.fontface</code>	See <code>grid::gpar</code>
<code>vertex.label.show</code>	Numeric scalar. Proportion of labels to show as the top ranking according to <code>vertex.size</code> .
<code>vertex.label.range</code>	Numeric vector of size 2 or 3. Relative scale of <code>vertex.label.fontSize</code> in points (see <code>grid::gpar</code>).
<code>edge.width.range</code>	Vector of length <code>ecount(x)</code> .
<code>edge.arrow.size</code>	Vector of length <code>ecount(x)</code> .
<code>edge.color</code>	A vector of length <code>ecount(x)</code> . Can be NULL in which case the color is picked as a mixture between ego and alters' <code>vertex.color</code> values.
<code>edge.curvature</code>	Numeric vector of length <code>ecount(x)</code> . Curvature of edges in terms of radians.
<code>edge.line.lty</code>	Vector of length <code>ecount(x)</code> .
<code>edge.line.breaks</code>	Vector of length <code>ecount(x)</code> . Number of vertices to draw (approximate) the arc (edge).
<code>sample.edges</code>	Numeric scalar between 0 and 1. Proportion of edges to sample.
<code>skip.vertex</code> , <code>skip.edges</code> , <code>skip.arrows</code>	Logical scalar. When TRUE the object is not plotted.
<code>add</code>	Logical scalar.
<code>zero.margins</code>	Logical scalar.
<code>y, ...</code>	Ignored
<code>newpage</code>	Logical scalar. When TRUE calls <code>grid::grid.newpage</code> .

Details

In the case of `edge.color`, the user can specify colors using [netplot-formulae](#).

Value

An object of class `c("netplot", "gTree", "grob", "gDesc")`. The object has an additional set of attributes:

- `.xlim`, `.ylim` vector of size two with the x-axis/y-axis limits.
- `.layout` A numeric matrix of size `vcount(x) * 2` with the vertices positions
- `.edgelist` A numeric matrix, The edgelist.

In the case of `nplot.default`, an object of class `netplot` and `grob` (see [grid::grob](#)) with the following slots:

- `children` The main grob of the object.
- `name` Character scalar. The name of the plot
- `.xlim` and `.ylim` Two vectors indicating the limits of the plot
- `.layout` A two-column matrix with the location of the vertices.
- `.edgelist` A two-column matrix, an edgelist.
- `.N` Integer. The number of vertices.
- `.M` Integer. The number of edges.

The children grob contains the following two objects:

- `background` a grob rectangle.
- `graph` a `gTree` that contains each vertex and each edge of the figure.

See Also

[nplot_base](#)

Examples

```
library(igraph)
library(netplot)
set.seed(1)
x <- sample_smallworld(1, 200, 5, 0.03)

plot(x) # ala igraph
nplot(x) # ala netplot
```

nplot_base

nplot using base graphics

Description

nplot using base graphics

Usage

```
nplot_base(
  x,
  layout = igraph::layout_nicely(x),
  vertex.size = igraph::degree(x, mode = "in"),
  bg.col = "transparent",
  vertex.nsidess = 15,
  vertex.color = grDevices::hcl.colors(1),
  vertex.size.range = c(0.01, 0.03),
  vertex.frame.color = grDevices::adjustcolor(vertex.color, red.f = 0.75, green.f =
    0.75, blue.f = 0.75),
  vertex.rot = 0,
  vertex.frame.prop = 0.1,
  edge.width = NULL,
  edge.width.range = c(1, 2),
  edge.arrow.size = NULL,
  edge.color = NULL,
  edge.color.mix = 0.5,
  edge.color.alpha = c(0.1, 0.5),
  edge.curvature = pi/3,
  edge.line.lty = "solid",
  edge.line.breaks = 10,
  sample.edges = 1,
  skip.vertex = FALSE,
  skip.edges = FALSE,
  skip.arrows = skip.edges,
  add = FALSE,
  zero.margins = TRUE
)
```

Arguments

x	An igraph object.
layout	Numeric two-column matrix with the graph layout.
vertex.size	Numeric vector of length vcount(x). Absolute size of the vertex.
bg.col	Color of the background.
vertex.nsidess	Numeric vector of length vcount(x). Number of sizes of the vertex. E.g. three is a triangle, and 100 approximates a circle.

<code>vertex.color</code>	Vector of length <code>vcount(x)</code> . Vertex colors.
<code>vertex.size.range</code>	Vector of length <code>vcount(x)</code> .
<code>vertex.frame.color</code>	Vector of length <code>vcount(x)</code> .
<code>vertex.rot</code>	Vector of length <code>vcount(x)</code> . Passed to <code>npolygon</code> , elevation degree from which the polygon is drawn.
<code>vertex.frame.prop</code>	Vector of length <code>vcount(x)</code> . What proportion of the vertex does the frame occupy (values between 0 and 1).
<code>edge.width</code>	Vector of length <code>ecount(x)</code> .
<code>edge.width.range</code>	Vector of length <code>ecount(x)</code> .
<code>edge.arrow.size</code>	Vector of length <code>ecount(x)</code> .
<code>edge.color</code>	A vector of length <code>ecount(x)</code> . Can be NULL in which case the color is picked as a mixture between <code>ego</code> and <code>alters'</code> <code>vertex.color</code> values.
<code>edge.color.mix</code>	Proportion of the mixing.
<code>edge.color.alpha</code>	Either a vector of length 1 or 2, or a matrix of size <code>ecount(x)*2</code> with values in <code>[0,1]</code> . Alpha (transparency) levels (see details)
<code>edge.curvature</code>	Numeric vector of length <code>ecount(x)</code> . Curvature of edges in terms of radians.
<code>edge.line.lty</code>	Vector of length <code>ecount(x)</code> .
<code>edge.line.breaks</code>	Vector of length <code>ecount(x)</code> . Number of vertices to draw (approximate) the arc (edge).
<code>sample.edges</code>	Numeric scalar between 0 and 1. Proportion of edges to sample.
<code>skip.vertex</code>	Logical scalar. When TRUE the object is not plotted.
<code>skip.edges</code>	Logical scalar. When TRUE the object is not plotted.
<code>skip.arrows</code>	Logical scalar. When TRUE the object is not plotted.
<code>add</code>	Logical scalar.
<code>zero.margins</code>	Logical scalar.

Value

`nplot_base` returns a list with the following components:

- `vertex.coords` A list of length `N` where each element describes the geomtry of each vertex.
- `vertex.color` A vector of colors
- `vertex.frame.coords` Similar to `vertex.coords`, but for the frame.
- `vertex.frame.color` Similar to `vertex.color`, but for the frame.
- `edge.color` Vector of functions used to compute the edge colors.

- `edge.coords` Similar to `vertex.coords`, the points that describe each edge.
- `edge.arrow.coords` A list of matrices describing the geometry of the tip of the edges.
- `edge.width` A numeric vector with edges' widths.
- `xlim, ylim` Limits of the plot area.

See Also

[nplot](#)

Examples

```
# Same example as in nplot
library(igraph)
library(netplot)
set.seed(1)
x <- sample_smallworld(1, 200, 5, 0.03)

nplot_base(x) # ala netplot (using base)
```

npolygon

n-sided polygons Calculate the coordinates for an nsided polygon

Description

n-sided polygons Calculate the coordinates for an nsided polygon

Usage

```
npolygon(x = 0, y = 0, n = 6L, r = 1, d = 2 * pi/(n)/2)
```

Arguments

<code>x, y</code>	Numeric scalar. Origin of the polygon.
<code>n</code>	Integer scalar. Number of sides.
<code>r</code>	Numeric scalar. Radius of the polygon.
<code>d</code>	Numeric scalar. Starting degree in radians.

Value

A two column matrix with the coordinates to draw a n sided polygon.

Examples

```

graphics.off()
oldpar <- par(no.readonly = TRUE)

par(xpd = NA, mfrow = c(3, 3), mai = rep(0, 4))
for (n in c(2, 3, 4, 5, 6, 8, 12, 20, 50)) {

  plot.new()
  plot.window(c(-1.25,1.25), c(-1.25,1.25))

  for (i in seq(1, .0005, length.out = 200)) {
    col <- adjustcolor("tomato", alpha.f = i)
    polygon(npolygon(x=(i-1)/4, y = (i-1)/4, r = i, d = i-1, n = n),
            col = NA, border=col)
  }

  mtext(sprintf("n = %i", n), side = 1, line = -3)
}

par(oldpar)

```

 piechart

A flexible piechart.

Description

While similar to `graphics::pie()`, this function is much more flexible as it allows providing different parameters for each slice of the pie. Furthermore, it allows adding the plot to the current device, making it possible to create compound piecharts.

Usage

```

piechart(
  x,
  labels = names(x),
  radius = 1,
  doughnut = 0,
  origin = c(0, 0),
  edges = 200,
  slice.off = 0,
  init.angle = 0,
  last.angle = 360,
  tick.len = 0.1,
  text.args = list(),
  segments.args = list(),
  skip.plot.slices = FALSE,
  add = FALSE,
  rescale = TRUE,

```

```
    ...
  )
```

Arguments

<code>x</code>	Numeric vector. Values that specify the area of the slices.
<code>labels</code>	Character vector of length <code>length(x)</code> . Passed to <code>graphics::text()</code> .
<code>radius</code>	Numeric vector. Radii of each slice (can be a scalar).
<code>doughnut</code>	Numeric scalar. Radii of each inner circle (doughnut) (can be a scalar).
<code>origin</code>	Numeric vector of length 2. Coordinates of the origin.
<code>edges</code>	Numeric scalar. Smoothness of the slices curve (can be a vector).
<code>slice.off</code>	Numeric vector. When <code>!=0</code> , specifies how much to move the slice away from the origin. When scalar is recycled.
<code>init.angle</code>	Numeric scalar. Angle from where to start drawing in degrees.
<code>last.angle</code>	Numeric scalar. Angle where to finish drawing in degrees.
<code>tick.len</code>	Numeric scalar. Size of the tick marks as proportion of the radius.
<code>text.args</code>	List. Further arguments passed to <code>graphics::text()</code> .
<code>segments.args</code>	List. Further arguments passed to <code>graphics::segments()</code> when drawing the tickmarks.
<code>skip.plot.slices</code>	Logical scalar. When <code>FALSE</code> , slices are not drawn. This can be useful if, for example, the user only wants to draw the labels.
<code>add</code>	Logical scalar. When <code>TRUE</code> it is added to the current device.
<code>rescale</code>	Logical scalar. When <code>TRUE</code> (default), the y-coordinates of the polygons (slices), text and tickmarks will be rescaled such that the aspect ratio is preserved, i.e. looks like a circle.
<code>...</code>	Further arguments passed to <code>graphics::polygon()</code> (see details).

Details

The function is a wrapper of `graphics::polygon()`, so all parameters such as color, density, border, etc. are passed directly by `mapply()` so that are specified one per slice. The coordinates of the slices are computed internally.

Value

A list with the following elements:

<code>slices</code>	A list of length <code>length(x)</code> with the coordinates of each slice.
<code>textcoords</code>	A numeric matrix of size <code>length(x)*2</code> with coordinates where the labels can be put at.
<code>alpha0</code>	A numeric vector of size <code>length(x)</code> with the starting degree in radians of the slice.
<code>alpha1</code>	A numeric vector of size <code>length(x)</code> with the ending degree in radians of the slice.

See Also

<https://commons.wikimedia.org/wiki/File:Nightingale-mortality.jpg>

Examples

```
# Example 1 -----
# A set of 3 nested rings rings starting at 315 deg. and ending at 270 deg.

# Values to plot
vals <- c(1,2,3,10)

# Outer (includes labels)
piechart(vals, col=grDevices::blues9[5:8], border=NA, doughnut = .5,
         radius=.75, labels=vals, init.angle = 315, last.angle = 270)

# Middle
piechart(vals, col=grDevices::blues9[3:6], border=NA, doughnut = .3,
         radius=.5, add=TRUE, init.angle = 315, last.angle = 270)

# Inner
piechart(vals, col=grDevices::blues9[1:4], border="gray", doughnut = .1,
         radius=.3, add=TRUE, init.angle = 315, last.angle = 270)

# Example 2 -----
# Passing values to polygon and playing with the radius and slice.off

piechart(1:10, density=(1:10)^2/2, slice.off = (1:10)/30, doughnut = .5,
         radius = sqrt(10:1),
         # Here we are setting random labels...
         labels=sapply(1:10, function(x) paste(sample(letters, x, TRUE), collapse="")))
)
```

segments_gradient

Draw segments colored by gradients

Description

Draw segments colored by gradients

Usage

```
segments_gradient(
  x,
  y = NULL,
  col = colorRamp2(c("transparent", "black"), TRUE),
  lend = 1,
  ...
)
```

Arguments

x, y	Coordinates passed to grDevices::xy.coords .
col	Color ramp function (see grDevices::colorRamp).
lend	Passed to graphics::segments .
...	Further arguments passed to segments.

Value

See [graphics::segments](#).

Examples

```
set.seed(1)
x <- cbind(cumsum(rnorm(1e3, sd=.1)), cumsum(rnorm(1e3, sd=.4)))
plot(x, type="n")
segments_gradient(x)
```

 set_gpar

Set/retrieve graphical parameters of a netplot object

Description

Set/retrieve graphical parameters of a netplot object

Usage

```
set_gpar(x, type, element, idx, ...)
set_edge_gpar(x, element, idx, ...)
set_vertex_gpar(x, element, idx, ...)
get_vertex_gpar(x, element, ..., idx)
get_edge_gpar(x, element, ..., idx)
get_gpar(x, type, element, ..., idx, simplify = TRUE)
```

Arguments

x	An object of class netplot.
type	Character. Either "edge" or "vertex".
element	Character. If "edge", then it can be either "line" or "arrow", otherwise it can be either "core" or "frame".

idx	(optional) Integer vector. Indices of the elements to be modified. When missing, all elements are modified.
...	Parameters to be modified/retrieved. This is passed to grid::editGrob via grid::gpar .
simplify	Logical. When TRUE it tries to simplify the result. Otherwise it returns a nested list.

Details

set_edge_gpar and set_vertex_gpar are shorthands for set_gpar(type = "edge", ...) and set_gpar(type = "vertex", ...) respectively.

get_edge_gpar and get_vertex_gpar are shorthands for get_gpar(type = "edge", ...) and get_gpar(type = "vertex", ...) respectively.

Value

An object of class netplot with modified parameters.

Examples

```
library(igraph)
library(netplot)

x <- make_ring(5)

g <- nplot(x)

# Updating edge color
g <- set_edge_gpar(g, col = "gray80")

# Retrieving the color of the vertices (core)
get_vertex_gpar(g, element = "core", "fill", "lwd")
```

Index

`alter (netplot-formulae)`, 6

`color_formula (netplot-formulae)`, 6

`colorkey`, 2

`colorRamp2`, 3

`ego (netplot-formulae)`, 6

`get_edge_gpar (set_gpar)`, 17

`get_gpar (set_gpar)`, 17

`get_vertex_gpar (set_gpar)`, 17

`graphics::pie()`, 14

`graphics::polygon()`, 15

`graphics::segments`, 17

`graphics::segments()`, 15

`graphics::text`, 3

`graphics::text()`, 15

`grDevices::colorRamp`, 3, 4, 17

`grDevices::xy.coords`, 17

`grid::editGrob`, 18

`grid::gpar`, 9, 18

`grid::grid.newpage`, 9

`grid::grob`, 10

`make_colors`, 5

`make_edges_colors (make_colors)`, 5

`make_vertex_colors (make_colors)`, 5

`mapply()`, 15

`netplot`, 6

`netplot (nplot)`, 7

`netplot-formulae`, 6, 10

`nplot`, 5, 7, 13

`nplot()`, 6

`nplot_base`, 10, 11

`npolygon`, 9, 12, 13

`piechart`, 14

`print.netplot (nplot)`, 7

`segments_gradient`, 16

`set_edge_gpar (set_gpar)`, 17

`set_edge_gpar()`, 6

`set_gpar`, 5, 17

`set_vertex_gpar (set_gpar)`, 17