

Package ‘shinyRadioMatrix’

January 14, 2021

Type Package

Title Create a Matrix with Radio Buttons

Version 0.2.0

Maintainer Zsolt Szelepcsényi <szelepcsenyi.zsolt@gmail.com>

Description An input controller for R Shiny: a matrix with radio buttons, where only one option per row can be selected.

Imports shiny

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Depends R (>= 2.10)

NeedsCompilation no

Author Zsolt Szelepcsényi [aut, cre],
Zoltán Szelepcsényi [aut]

Repository CRAN

Date/Publication 2021-01-14 10:00:02 UTC

R topics documented:

exPftList	2
exTaxonList	2
radioMatrixInput	3

Index	6
--------------	----------

 exPftList

PFT List

Description

A PFT list, which gives the column names in a taxon-PFT matrix.

Format

A data frame with 31 rows and 2 columns:

ID Unique identifier for the plant functional types (PFTs).

Name Name of the PFT.

Examples

```
data(exPftList)
str(exPftList)
```

 exTaxonList

Taxon List

Description

A taxon list, which gives the row names in a taxon-PFT matrix.

Format

A data frame with 31 rows and 2 columns:

Var Unique identifier for the variable.

VarName Name of the pollen type or variable, including Linnean and non-Linnean names (Acer saccharum-type, Cerealea, Avena/Triticum).

DefPFT Default PFT assignment for the variable.

Examples

```
data(exTaxonList)
str(exTaxonList)
```

radioMatrixInput	<i>Create radioMatrixInput</i>
------------------	--------------------------------

Description

Create radioMatrixInput

Usage

```
radioMatrixInput(
  inputId,
  rowIDs,
  rowLLabels,
  rowRLabels = NULL,
  choices = NULL,
  selected = NULL,
  choiceNames = NULL,
  choiceValues = NULL,
  labelsWidth = list(NULL, NULL)
)
```

Arguments

inputId	The input slot that will be used to access the value.
rowIDs	character. Vector of row identifiers that will be used to find values that the user has selected. In the output, the component will return a named list of values, each name corresponding to the row id, and the value - to the value user has selected in this row.
rowLLabels	character. Vector (or a matrix with one column) of labels that displayed in the leftmost point of each row. The column name of the matrix could be displayed in the header of the assignment matrix.
rowRLabels	character. Vector (or a matrix with one column) of labels that displayed in the rightmost point of each row. The column name of the matrix could be displayed in the header of the assignment matrix. Using this argument is optional. But it allows to create Likert scales, potentially with several scales arranged in a matrix.
choices	List of values to select from (if elements of the list are named then that name rather than the value is displayed to the user). If this argument is provided, then choiceNames and choiceValues must not be provided, and vice-versa. The values should be strings; other types (such as logicals and numbers) will be coerced to strings.
selected	Vector of the initially selected values (if not specified then defaults to NULL).
choiceNames, choiceValues	List of names and values, respectively, that are displayed to the user in the app and correspond to the each choice (for this reason, the objects 'choiceNames'

and 'choiceValues' must have the same length). If either of these arguments is provided, then the other must be provided and choices must not be provided. The advantage of using both of these over a named list for choices is that the object 'choiceNames' allows any type of UI object to be passed through (tag objects, icons, HTML code, ...), instead of just simple text.

labelsWidth List of two valid values of CSS length unit. Each element has to be a properly formatted CSS unit of length (e.g., '10%', '40px', 'auto'), specifying the minimum (first value) and maximum (second value) width of the labels columns. The valid elements will be written to the style attribute of the labels td tags.

Value

HTML markup for radioMatrixInput

Examples

```
library(shiny)
library(shinyRadioMatrix)

## Only run examples in interactive R sessions
if (interactive()) {

  data(exTaxonList)
  data(exPftList)

  ui <- fluidPage(
    radioMatrixInput(inputId = "rmi01", rowIDs = head(exTaxonList$Var),
                     rowLLabels = head(as.matrix(subset(exTaxonList, select = "VarName"))),
                     choices = exPftList$ID,
                     selected = head(exTaxonList$DefPFT)),
    verbatimTextOutput('debug01')
  )

  server <- function(input, output, session) {
    output$debug01 <- renderPrint({input$rmi01})
  }

  shinyApp(ui, server)
}

if (interactive()) {

  ui <- fluidPage(

    radioMatrixInput(inputId = "rmi02", rowIDs = c("Performance", "Statement A"),
                     rowLLabels = c("Poor", "Agree"),
                     rowRLabels = c("Excellent", "Disagree"),
                     choices = 1:5,
                     selected = rep(3, 2),
                     labelsWidth = list("100px", "100px")),
    verbatimTextOutput('debug02')
```

```
)  
server <- function(input, output, session) {  
  output$debug02 <- renderPrint({input$rmi02})  
}  
shinyApp(ui, server)  
}
```

Index

`exPftList`, 2

`exTaxonList`, 2

`radioMatrixInput`, 3