

# Package ‘showtextdb’

September 11, 2017

**Type** Package

**Title** Font Files for the 'showtext' Package

**Version** 2.0

**Date** 2017-09-09

**Author** Yixuan Qiu and authors/contributors of the included fonts. See file AUTHORS for details.

**Maintainer** Yixuan Qiu <yixuan.qiu@cos.name>

**Description** Providing font files that can be used by the 'showtext' package.

**Imports** sysfonts (>= 0.7.1), utils

**Suggests** curl

**License** Apache License (>= 2.0)

**Copyright** see file COPYRIGHTS

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2017-09-11 14:13:21 UTC

## R topics documented:

font_install	2
load_showtext_fonts	3
source_han	4

<b>Index</b>	<b>5</b>
--------------	----------

---

`font_install`*Install Fonts to the 'showtextdb' Package*

---

### Description

`font_install()` saves the specified font to the 'fonts' directory of the **showtextdb** package, so that it can be used by the **showtext** package. This function requires the **curl** package.

`font_installed()` lists fonts that have been installed to **showtextdb**.

**NOTE:** Since the fonts are installed locally to the package directory, they will be removed every time the **showtextdb** package is upgraded or re-installed.

### Usage

```
font_install(font_desc, quiet = FALSE, ...)
```

```
font_installed()
```

### Arguments

`font_desc` A list that provides necessary information of the font for installation. See the **Details** section.

`quiet` Whether to show the progress of downloading and installation.

`...` Other parameters passed to `curl::curl_download()`.

### Details

`font_desc` is a list that should contain at least the following components:

`showtext_name` The family name of the font that will be used in **showtext**.

`font_ext` Extension name of the font files, e.g., `ttf` for TrueType, and `otf` for OpenType.

`regular_url` URL of the font file for "regular" font face.

Optionally, `font_desc` can also contain `bold_url`, `italic_url`, `bolditalic_url`, and `symbol_url` that provide the URLs of the other font faces.

See [source\\_han\\_sans\(\)](#) and [source\\_han\\_serif\(\)](#) for an example of the `font_desc` parameter.

### Author(s)

Yixuan Qiu <<http://statr.me/>>

### Examples

```
## Not run:
## Install Source Han Serif Simplified Chinese
font_install(source_han_serif())

## List available font families
sysfonts::font_families()

## Use the font with the "showtext" package
if(require(showtext)) {
  wd = setwd(tempdir())
  showtext.auto()

  pdf("source-han-serif.pdf")
  par(family = "source-han-serif-cn")
  plot.new()
  box()
  text(0.5, 0.9, "\u601d\u6e90\u5b8b\u4f53", cex = 3, font = 2)
  text(0.5, 0.4, "\u843d\u5176\u5b9e\u8005\u601d\u5176\u6811", cex = 3)
  text(0.5, 0.2, "\u996e\u5176\u6d41\u8005\u6000\u5176\u6e90", cex = 3)
  dev.off()
  setwd(wd)
}

## End(Not run)
```

---

load\_showtext\_fonts    *Load Fonts for the 'showtext' Package*

---

### Description

This function loads fonts that will be used by the **showtext** package.

### Usage

```
load_showtext_fonts()
```

### Author(s)

Yixuan Qiu <<http://statr.me/>>

### Examples

```
## Not run:
sysfonts::font_families()

load_showtext_fonts()
sysfonts::font_families()

## End(Not run)
```

---

source\_han

*Meta-information for the Source Han Sans/Serif Fonts*

---

### **Description**

These functions provide information of the Source Han Sans/Serif fonts that can be used in the `font_install()` function. Source Han Sans/Serif fonts provide complete support for the CJK (Chinese, Japanese, and Korean) characters.

### **Usage**

```
source_han_sans(lang = c("CN", "TW", "JP", "KR"))
```

```
source_han_serif(lang = c("CN", "TW", "JP", "KR"))
```

### **Arguments**

`lang` Language of the font. "CN" for simplified Chinese, "TW" for traditional Chinese, "JP" for Japanese, and "KR" for Korean.

### **Author(s)**

Yixuan Qiu <<http://statr.me/>>

### **Examples**

```
## Not run:
## Install Source Han Sans font (by default Simplified Chinese)
## to the showtexdb package
font_install(source_han_sans())

## Source Han Serif Japanese
font_install(source_han_serif("JP"))

## End(Not run)
```

# Index

`font_install`, [2](#), [4](#)  
`font_installed(font_install)`, [2](#)  
  
`load_showtext_fonts`, [3](#)  
  
`source_han`, [4](#)  
`source_han_sans`, [2](#)  
`source_han_sans(source_han)`, [4](#)  
`source_han_serif`, [2](#)  
`source_han_serif(source_han)`, [4](#)