

Package ‘tsfgrnn’

November 25, 2019

Type Package

Title Time Series Forecasting Using GRNN

Version 0.1.0

Maintainer Francisco Martinez <fmartin@ujaen.es>

Description A general regression neural network (GRNN) is a variant of a Radial Basis Function Network characterized by a fast single-pass learning. 'tsfgrnn' allows you to forecast time series using a GRNN model Francisco Martinez et al. (2019) <doi:10.1007/978-3-030-20521-8_17> and Weizhong Yan (2012) <doi:10.1109/TNNLS.2012.2198074>. When the forecasting horizon is higher than 1, two multi-step ahead forecasting strategies can be used. The model built is autoregressive, that is, it is only based on the observations of the time series. You can consult and plot how the prediction was done. It is also possible to assess the forecasting accuracy of the model using rolling origin evaluation.

License GPL-2

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Suggests testthat, knitr, rmarkdown

Imports ggplot2

VignetteBuilder knitr

URL <https://github.com/franciscomartinezdelrio/tsfgrnn>

BugReports <https://github.com/franciscomartinezdelrio/tsfgrnn>

NeedsCompilation no

Author Maria Pilar Frias-Bustamante [aut],
Ana Maria Martinez-Rodriguez [aut],
Antonio Conde-Sanchez [aut],
Francisco Martinez [aut, cre]

Repository CRAN

Date/Publication 2019-11-25 21:30:02 UTC

R topics documented:

autoplot.grnnForecast	2
grnn_examples	3
grnn_forecasting	3
grnn_weights	4
plot.grnnForecastRO	5
plot_example	5
predict.grnnForecast	6
rolling_origin	7
Index	9

autoplot.grnnForecast *Create a ggplot object from a grnnForecast object*

Description

It uses a grnnForecast object to create a ggplot object that plots a time series and its forecast using GRNN regression.

Usage

```
## S3 method for class 'grnnForecast'
autoplot(forecast, highlight = c("none",
  "points"))
```

Arguments

forecast	The grnnForecast object.
highlight	A string value indicating what elements should be highlighted. Possible values are "none" and "points".

Value

The ggplot object representing a plotting with the forecast.

Examples

```
pred <- grnn_forecasting(USAccDeaths, h = 12, lags = 1:12, sigma = 50)
library(ggplot2)
autoplot(pred)
```

grnn_examples	<i>Examples of a GRNN model</i>
---------------	---------------------------------

Description

It shows the examples of the model associated to a grnnForecast object.

Usage

```
grnn_examples(forecast)
```

Arguments

forecast A grnnForecast object.

Value

A matrix including the features and targets of the examples associated with the model of a grnnForecast object.

Examples

```
pred <- grnn_forecasting(ts(1:8), h = 1, lags = 1:2)
grnn_examples(pred)
```

grnn_forecasting	<i>Time series forecasting using GRNN regression</i>
------------------	------------------------------------------------------

Description

It applies GRNN regression to forecast the future values of a time series. The lags used as autoregressive variables are set with the lags parameter. If the user does not set the lags, these values are selected automatically.

Usage

```
grnn_forecasting(timeS, h, lags = NULL, sigma = NULL,
  msas = c("recursive", "MIMO"), scale = TRUE)
```

Arguments

timeS	A numeric vector or time series of class <code>ts</code> .
h	A positive integer. Number of periods for forecasting.
lags	An integer vector in increasing order expressing the lags used as autoregressive variables.
sigma	A positive real value. The smoothing parameter in GRNN regression. If NULL (the default) the parameter is chosen using an optimization tool.
msas	A string indicating the Multiple-Step Ahead Strategy used when more than one value is predicted. It can be "MIMO" or "recursive" (the default).
scale	A logical. If TRUE (the default), the time series is scaled to the range [0, 1].

Value

An object of class "grnnForecast". The function `summary` can be used to obtain or print a summary of the results. An object of class "grnnForecast" is a list containing at least the following components:

call	the matched call.
msas	the Multi-Step Ahead Strategy.
prediction	a time series with the forecast.
model	an object of class "grnnModel" with the GRNN model

Examples

```
pred <- grnn_forecasting(USAccDeaths, h = 12, lags = 1:12)
plot(pred)
```

grnn_weights	<i>Training examples and their corresponding weights used in a prediction</i>
--------------	-------------------------------------------------------------------------------

Description

It shows the input vector and the weights of the training examples used in a prediction associated with a "grnnForecast" object.

Usage

```
grnn_weights(forecast)
```

Arguments

forecast	A grnnForecast object.
----------	------------------------

Value

A list including the input vectors used in GRNN regression and the training examples, with their weights, used in the prediction.

Examples

```
pred <- grnn_forecasting(UKgas, h = 4, lags = 1:4, msas = "MIMO")
grnn_weights(pred)
```

plot.grnnForecastRO *Plot the prediction for a test set*

Description

It plots the forecast associated with a test set generated with the function [rolling_origin](#).

Usage

```
## S3 method for class 'grnnForecastRO'
plot(x, h = NULL, ...)
```

Arguments

x the object obtained from a call to [rolling_origin](#).

h an integer. The forecasting horizon. If NULL (the default), the maximum forecasting horizon of all the test sets is used.

... Other plotting parameters to affect the plot.

Value

None

plot_example *Plot an example used in a prediction of a grnnForecast object*

Description

This function is useful to see how the forecast has been computed. An ordinal specifying the order of the weight has to be supplied and the function plots the training pattern associated with that ordinal.

Usage

```
plot_example(forecast, position, h = 1, timeS = c("preprocessed",
"original"))
```

Arguments

forecast	The grnnForecast object.
position	An integer. It is an ordinal number indicating what training pattern to plot. For instance, if position is 1 it means that the training pattern with the greatest weight should be plotted. If position is 2 the training pattern with the second greatest weight is plotted and so on.
h	An integer. This value is only useful when the recursive strategy is being used. It indicates the forecasting horizon
timeS	A string value indicating what time series to plot. Possible values are "preprocessed" (the default) and "original". That is, you can plot the preprocessed or the original time series.

Value

A ggplot object representing an example used in the prediction.

Examples

```
pred <- grnn_forecasting(USAccDeaths, h = 12, lags = 1:12, sigma = 50)
library(ggplot2)
plot_example(pred, 1)
```

predict.grnnForecast *Predict method for GRNN models for time series forecasting.*

Description

Predicted values based on a GRNN model for time series forecasting.

Usage

```
## S3 method for class 'grnnForecast'
predict(object, h, ...)
```

Arguments

object	a grnnForecast object obtained by a call to the grnn_forecasting function.
h	an integer. The forecasting horizon.
...	further arguments passed to or from other methods.

Details

If the models uses the MIMO strategy for multiple-step ahead prediction, the forecasting horizon is fixed to the model forecasting horizon.

Value

a grnnForecast object with the prediction and information about the GRNN model, see the documentation of [grnn_forecasting](#) for the structure of grnnForecast objects.

Examples

```
pred <- grnn_forecasting(UKgas, h = 4, msas = "MIMO")
new_pred <- predict(pred, h = 4)
print(new_pred$prediction)
plot(new_pred) # To see a plot with the forecast
```

 rolling_origin

Assessing forecasting accuracy with rolling origin

Description

It uses the model and the time series associated with a grnnForecast object to assess the forecasting accuracy of the model using the last h values of the time series to build test sets applying a rolling origin evaluation.

Usage

```
rolling_origin(grnnf, h = NULL, rolling = TRUE)
```

Arguments

grnnf	A grnnForecast object.
h	A positive integer. The forecast horizon. If NULL (the default) the prediction horizon of the grnnForecast object is used.
rolling	A logical. If TRUE (the default), forecasting horizons from 1 to h are used. Otherwise, only horizon h is used.

Details

This function assesses the forecast accuracy of the model used by the grnnForecast object. It uses h different test and training sets. The first test set consists of the last h values of the time series (the training set is formed by the previous values). The next test set consists of the last $h - 1$ values of the time series and so on (the last test set is formed by the last value of the time series).

Value

A list containing at least the following fields:

test_sets	a matrix containing the test sets used in the evaluation. Every row contains a different test set.
predictions	The predictions for the test sets.

errors	The errors for the test sets.
global_accu	Different measures of accuracy applied to all the errors.
h_accu	Different measures of accuracy applied to all the errors for every forecasting horizon.

Examples

```
pred <- grnn_forecasting(UKgas, h = 4, lags = 1:4, scale = FALSE)
ro <- rolling_origin(pred)
print(ro$global_accu)
```


Index

`autoplot.grnnForecast`, 2

`grnn_examples`, 3

`grnn_forecasting`, 3, 6, 7

`grnn_weights`, 4

`plot.grnnForecastRO`, 5

`plot_example`, 5

`predict.grnnForecast`, 6

`rolling_origin`, 5, 7

`summary`, 4